



Halogen Lamps

Linear and Capsule Lamps

Watts	Bulb	Base	Product Number	Symbols, Footnotes	Ordering Code	Volts	Pkg. Qty.†	Description	Class Filament	MOL (In.)	Rated Avg. Life (Hrs.) ⁽⁹³⁾	Approx. MBCP*	Lumens	Life Years (446)	Energy Cost (445)	Color Temp. (K)
-------	------	------	----------------	--------------------	---------------	-------	------------	-------------	----------------	-----------	--	---------------	--------	------------------	-------------------	-----------------

Halogen Single-Ended Linear Lamps (95)

FTC REQUIREMENTS

100	T4	D.C. Bay	44278-0		100Q/CL/DC ESR	120	12	Clear	C, CC-8	2 $\frac{1}{16}$	1000	—	1600	0.9	\$12.05	2700
150	T4	Mini-Can	20049-3		150Q/CL	130	12	Clear	C, CC-8	3	1000	—	2800	0.9	\$18.07	2700
250	T4	Mini-Can	14668-8		250Q/CL EHT	120	12	Clear	C, CC-8	3 $\frac{1}{8}$	1000	—	5000	0.9	\$30.11	2850
			14667-0		250Q/CL	130	12	Clear	C, CC-8	3 $\frac{1}{8}$	1000	—	5000	0.9	\$30.11	2850

Halogen Double-Ended Linear Lamp Blister-Carded (99)

100	T3	RSC	41560-4	†	BC100T3Q/CL	120	12	Blister Card	C, C-8	3 $\frac{1}{8}$	2000	—	1600	1.8	\$12.05	2900
150	T3	RSC	41561-2	†	BC150T3Q/CL	120	12	Blister Card	C, C-8	3 $\frac{1}{8}$	2000	—	2400	1.8	\$18.07	2900
			41575-2	†	BC150T3Q/CL LONG	120	12	Blister Card	C, C-8	4 $\frac{1}{8}$	1500	—	2400	1.4	\$18.07	2900
			41885-5	\$ †	BC150T3Q/HES/CL	120	6	Blister Card	C, C-8	4 $\frac{1}{8}$	1500	—	2850	1.4	\$18.07	3000
300	T3	RSC	20355-4		BC300T3Q/CL	120	12	Blister Card	C, C-8	4 $\frac{1}{8}$	2000	—	5200	1.8	\$36.14	2900
			41571-1	†	BC300T3Q/CL/TP	120	12	Blister Card	C, C-8	4 $\frac{1}{8}$	2000	—	5200	1.8	\$36.14	2900
500	T3	RSC	41572-9	†	BC500T3Q/CL/TP	120	12	Blister Card	C, C-8	4 $\frac{1}{8}$	2000	—	9500	1.8	\$60.23	2900

Halogen Double-Ended Linear Lamp (99)

300	T3	RSC	39282-9		300T3Q/CL EHM	120	12	Clear	C, C-8	4 $\frac{1}{8}$	2000	—	5200	1.8	\$36.14	2900	
500	T3	RSC	13223-3		500T3Q/CL	125	12	Clear	C, C-8	4 $\frac{1}{8}$	2000	—	9200	1.8	\$60.23	2850	
						130											
			20010-5		500T3Q/CL FCL	120	12	Clear	C, C-8	4 $\frac{1}{8}$	2000	—	9500	1.8	\$60.23	2900	
1000	T3	RSC	41972-1	†	1000T3Q/CL	240	12	Clear	C, C-8	7 $\frac{1}{16}$	2000	—	21,500	1.8	\$120.45	2,950	
1500	T3	RSC	41996-9	†	1500T3Q/CL	277	12	Clear	C, C-8	10	2000	—	33,000	1.8	\$180.68	2,950	

Halogen Mains-Voltage Capsule Lamp Blister-Carded (95)

35	T4	GY8.6	41632-1	†	BC35W/T4/120V/CAPSULE	120	12	Blister Card	C, CC2V	1 $\frac{1}{16}$	2500	—	400	2.3	\$4.22	3000
50	T4	GY8.6	41631-3	†	BC50W/T4/120V/CAPSULE	120	12	Blister Card	C, C-8	2 $\frac{1}{4}$	2500	—	600	2.3	\$6.02	3000
75	T4	GY8.6	41667-7	†	BC75W/T4/120V/CAPSULE	120	12	Blister Card	C, C-8	2 $\frac{1}{4}$	2000	—	1200	1.8	\$9.03	3000
			41870-7	\$ †	BC75T4Q/HES/CAP	120	12	Blister Card	C, C-8	2 $\frac{1}{4}$	1500	—	1550	1.4	\$9.03	3000
100	T4	GY8.6	41668-5	†	BC100W/T4/120V/CAPSULE	120	12	Blister Card	C, C-8	2 $\frac{1}{4}$	2500	—	1650	2.3	\$12.05	3000

Halogen Low-Voltage Capsule Lamp Blister-Carded (95)

10	T3	G4	41567-9	†	BC10W/T3/12V	12	12	Blister Card	C, C-8	1 $\frac{1}{4}$	2000	—	100	1.8	\$1.20	3000
20	T3	G4	41566-1	†	BC20W/T3/12V	12	12	Blister Card	C, C-8	1 $\frac{1}{4}$	2000	—	250	1.8	\$2.41	3000
30	T4	GY6.35	41882-2	\$ †	BC30T4/HES/12V	12	12	Blister Card	C, C-8	1 $\frac{3}{8}$	4000	—	750	3.7	\$3.61	3000
50	T4	GY6.35	41559-6	†	BC50W/T4/12V	12	12	Blister Card	C, C-8	1 $\frac{3}{8}$	2000	—	700	1.8	\$6.02	3000
75	T4	GY6.35	41558-8	†	BC75W/T4/12V	12	12	Blister Card	C, C-8	1 $\frac{3}{8}$	2000	—	1100	1.8	\$9.03	2800

For the most current product information, go to the e-catalog on www.philips.com
Halogen symbols and footnotes located on page 109

