






HALOGEN LAMPS



Bulb	Base	Product Number	Footnotes	Product Code	Description	Pkg. Qty.	Volts	Lumens	Color Temp	Avg. Life	Design Filament	MOL	Beam Spread
PRISM® & HaloXen. JC Type													
5 WATT													
T3	G4	107006	3	JC5	Clear	10/1000	12	60	2800	3000	C-8	1.18"	-
10 WATT													
T3	BA15s	147008	3	JC10/BA15S	Clear	10/1000	12	120	2800	3000	C-8	1.50"	-
		107944	2,3	JC10/BA15S/HX	Clear HaloXen®	10/1000	12	120	2850	10000	C-8	1.50"	-
	G4	107008	3	JC10	Clear	10/1000	12	120	2800	3000	C-8	1.18"	-
		107710	2,3	JC10/HX	Clear HaloXen®	10/1000	12	120	2850	10000	C-8	1.18"	-
		90002	3	JC10/X	Clear Xenon	10/500	12	120	2700	20000	C-8	1.18"	-
20 WATT													
T3	BA15s	147010	3	JC20/BA15S	Clear	10/1000	12	300	2800	3000	C-8	1.50"	-
		107718	2,3	JC20/BA15S/HX	Clear HaloXen®	10/1000	12	350	2900	10000	C-8	1.50"	-
	G4	107010	3	JC20	Clear	10/1000	12	300	2800	3000	C-8	1.18"	-
		107712	2,3	JC20/HX	Clear HaloXen®	10/1000	12	350	2900	10000	C-8	1.18"	-
		70922	2,3	JC20/24V/HX	Clear HaloXen®	10/1000	24	350	4100	5000	CC-6	1.25"	-
		90003	3	JC20/X	Clear Xenon	10/500	12	250	2700	10000	C-8	1.18"	-
T4	G6.35	107009	3	JC20/6.35	Clear	10/1000	12	300	2800	3000	C-8	1.65"	-
	GY6.35	107036	3	JCD20	Clear	10/500	130	180	2750	2000	CC-2	1.69"	-
	G8	107076	3	JCD20/G8	Clear	10/500	130	180	2750	2000	CC-2	1.69"	-
25 WATT													
T4	G9	71001	3	JCD25/G9	Clear	10/500	130	280	2650	2000	CC-2V	1.69"	-
		107902	3	JCD25FR/G9	Frost	10/500	130	280	2650	2000	CC-2V	1.69"	-
35 WATT													
T4	BA15d	147012	3	JC35/BA15D	Clear	10/1000	12	600	2850	3000	C-8	1.65"	-
		107720	X 3	JC35/BA15D/HX	Clear HaloXen®	10/1000	12	600	2900	10000	C-8	1.50"	-
	G4	107000	3	JC35/G4	Clear	10/1000	12	600	2850	3000	C-8	1.58"	-
	G6.35	107012	3	JC35	Clear	10/1000	12	600	2850	3000	C-8	1.58"	-
		107714	2,3	JC35/HX	Clear HaloXen®	10/1000	12	600	2900	10000	C-8	1.60"	-
	GY6.35	107011	3	JCD35	Clear	10/500	130	350	2800	2000	CC-2V	1.81"	-
	G8	107072	3	JCD35/G8	Clear	10/500	130	350	2800	2000	CC-2V	1.69"	-
40 WATT													
T4	G9	107906	3	JCD40/G9	Clear	10/500	130	480	2750	2000	CC-2V	1.69"	-
		107908	3	JCD40/FR/G9	Frost	10/500	130	450	2750	2000	CC-2V	1.69"	-
		107310	3	JCD40/FR/G9/120	Frost	10/1000	120	450	2800	2000	CC-2V	1.69"	-

Ⓔ Means this lamp meets Federal Minimum Efficiency standards.
Halogen lamp symbols, footnotes and abbreviations are located on pages 131-133.