



# KT-LED82P-H-8CSE-D

## 2-PIN LED LAMP

### DESCRIPTION

8.5W 2-Pin LED Lamp | Color Select 3000/3500/4000K | ≥82 CRI



<b>LAMP TYPE:</b> Compact
<b>BULB TYPE:</b> 2-Pin LED
<b>BASE TYPE:</b> G24d
<b>WATTAGE:</b> 8.5W
<b>SELECTABLE COLOR TEMPERATURE:</b> 3000/3500/4000K
<b>COLOR RENDERING INDEX (CRI):</b> ≥82
<b>WARRANTY:</b> 5 Years



### PRODUCT FEATURES

- **\*\*G24D 2-pin can be used in G24Q 4-pin applications for ballast bypass\*\***
- Save 50% on energy consumption compared to typical CFL bulbs
- Extend useful life four times (50,000 hours)
- Environmentally friendly: no mercury used
- Frosted lens eliminates pixelation
- Not for use in enclosed fixtures
- Operating temperature: -20°C/-4°F to 45°C/113°F
- Simplifies installation without the need for an external driver or ballast
- Instant startup
- Suitable for use in dry and damp locations
- UL Classified
- Rotatable 270°

### OPERATING SPECIFICATIONS

#### ELECTRICAL CHARACTERISTICS

Input Voltage	Lamp Wattage	Power Factor	System Wattage
120-277V	8.5W	>0.9	8.5W

#### PHOTOMETRIC CHARACTERISTICS


Color Temperature (CCT)	3000K*	3500K	4000K
Luminous Flux	960	1020	1050
Color Rendering Index (CRI)	≥82	≥82	≥82
Bare Lamp Efficacy	113	120	124

\*Preset to 3000K

#### RATED LIFE

L70 (Hours)	50,000
-------------	--------

#### POLAR CANDELA DISTRIBUTION






# KT-LED82P-H-8CSE-D

## 2-PIN LED LAMP


**WIRING**

**BYPASS MAGNETIC BALLAST WITH 1 LAMP**

**BEFORE**




**AFTER**




**BYPASS ELECTRONIC BALLAST WITH 1 LAMP**

**BEFORE**




**AFTER**




**BYPASS MAGNETIC BALLAST WITH 2 LAMPS**

**BEFORE**




**AFTER**




**BYPASS ELECTRONIC BALLAST WITH 2 LAMPS**

**BEFORE**




**AFTER**



**PHYSICAL CHARACTERISTICS**

**LAMP DIMENSIONS**





# KT-LED82P-H-8CSE-D

## 2-PIN LED LAMP

**ORDERING INFORMATION**

ORDER CODE	PACK QTY.	UPC	EASY CODE
KT-LED82P-H-8CSE-D	24	843654137674	WHP-85

**CATALOG NUMBER BREAKDOWN**

# KT-LED82P-H-8CSE-D

1
2
3
4
5
6
7
8
9

- 1 Keystone Technologies
- 2 LED Lamp
- 3 Wattage
- 4 2-Pin Lamp Type
- 5 Horizontal Orientation
- 6 80 CRI
- 7 Color Select
- 8 Color Select Designation
- 9 Direct Drive Series

**8 Color Select Designation**

E	3000/3500/4000K
---	-----------------