



# SlimSurface LED Downlight

SlimSurface LED 7" round downlight, 80 CRI, 4000K, 1000 lm, 120/277V, 0-10V dimming, wet location, aluminum finish

SlimSurface LED 7" round downlight, 80 CRI, 4000K, 1000 lm, 120/277V, 0-10V dimming, wet location, aluminum finish

SlimSurface LED is a low profile downlight intended for ceiling or wall mount applications. This 0.625" thick luminaire offers the appearance of a recessed downlight but is actually surface mounted.

## Product data

General Information	
Lamp Source Code	LED
Color Temperature	4000K
CRI	80
Downlight Type	Open Downlight
Photometric Distribution Type	Direct
Mounting	Surface Wall

  

Operating and Electrical	
Luminaire Input Watts	14
Voltages	120/277 V

  

Mechanical and Housing	
Aperture Size Code	7 in
Shape	Round

Initial Performance (IEC Compliant)	
Luminaire Lumens	1000

  

Product Data	
Order product name	SlimSurface LED 7" round downlight, 80 CRI, 4000K, 1000 lm, 120/277V, 0-10V dimming, wet location, aluminum finish
Commercial Code	S7R840K10ALZ10U
Order code	S7R840K10ALZ10U
Catalog Number Description	SlimSurface LED 7" round downlight, 80 CRI, 4000K, 1000 lm, 120/277V, 0-10V dimming, wet location, aluminum finish
Service / Spec Smart	-
Material Nr. (12NC)	LIGU60014061

## SlimSurface LED Downlight

