

STARLED[®], INC.

ORDERING INFORMATION:

$$\frac{\text{SMBL00}}{\text{(A)}} - \frac{\text{X}}{\text{(B)}} - \frac{\text{XX}}{\text{(C)}}$$

(A) MODEL

SMBL00

(B) VOLTAGE & EXTERNAL RESISTOR VALUE NEEDED

0 = 24V to 28VAC/DC-----10 Ohms

1 = 125VAV/DC-----2000 Ohms

2 = 48VDC/VAC-----2000 Ohms

3 = 240V to 250VAC / DC-----5100 Ohms

(C) LED EMITTED COLOR & WAVE LENGHT

01 = ULTRA RED (655-660nm)

U2 = ULTRA HI EFF, RED (620-630nm)

U3 = ULTRA ORANGE (612-620)

U4 = ULTRA YELLOW (590-595nm)

*6NW = ULTRA PURE GREEN (520-530nm)

*8NW = FLUORESCENT "WHITE" (nm N/A)

*10NW = ULTRA BLUE (465-475nm)

*11NW = BLUISH GREEN (498-508nm)

*12NW = SOFT WHITE (nm N/A)

Note: LED EMITTED COLOR SAME AS COLOR OF SLEEVE.

*CONTINUOUS CURRENT IS 10mA.

Housing Mat'l. UL94V0

Specifications are subject to change without notice.

