



T-1³/₄ WEDGE BASE MULTI-CHIP LEDs

ORDERING INFORMATION: WB19 2 C 1 - 24V/15
 (A) (B) (C) (D) (E)

(A) MODEL

WB19 = MOL. 0.730" Max.
WB73 = MOL. 0.700" Max.
WB83 = MOL. 0.805" Max.

(B) NUMBER OF LEDS

*2 = 1, 2 CHIPS LED (AVAILABLE IN ULTRA PURE GREEN ONLY)
**3 = 1, 3 CHIPS LED (AVAILABLE IN ULTRA PURE GREEN ONLY)
6 = 1, 6 CHIPS T-1³/₄ LED

(C) LED LENS COLOR

C = CLEAR

(D) LED EMITTING COLOR & WAVELENGTH

1 = ULTRA RED (660nm)
2 = STD. RED (630-635nm)
U2 = ULTRA HI EFF. RED (623-630nm)
3 = STD. ORANGE (605-610nm)
U3 = ULTRA ORANGE (612-620nm)
4 = STD. YELLOW (585)
U4 = ULTRA YELLOW (590-595nm)
5 = STD. GREEN (565-570nm)
*6NW = ULTRA PURE GREEN (520-530nm)

(E) STANDARD DC & AC OPERATING VOLTAGES/mA

WB196 & WB736: 6V/45, 12V/30, 14V/30, 24V/15, 28V/15, 36V/12, 48V/12 & 60V/15
WB836: 6V/45, 12V/30, 14V/30, 24V/15, 28V/15, 36V/12, 48V/12, 60V/15 & 120V/6

* **MAX. CONTINUOUS CURRENT 20mA.**

** **MAX. CONTINUOUS CURRENT 10mA.**

APPLICATION MUST BE SPECIFIED WHEN ORDERING:

VAC = ALTERNATING CURRENT VDC(V) = DIRECT CURRENT

NOTE: PLEASE CALL FACTORY FOR OTHER VOLTAGES.

DIRECT INCANDESCENT LAMP REPLACEMENTS


WB196 & WB736: 17, 37, 73, 74, 79, 84, 85, 86, ETC...

WB836: 18, 73, 79, 84, 85, 86, ETC...


HOUSING MAT'L. UL94-VO APPROVED

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

MODEL: WB19



MODEL: WB73



MODEL: WB83

